# (19) World Intellectual Property Organization

International Bureau





# (43) International Publication Date 30 June 2005 (30.06.2005)

### **PCT**

# (10) International Publication Number WO 2005/058175 A1

(51) International Patent Classification<sup>7</sup>: A61B 17/86

(21) International Application Number:

PCT/GB2004/005280

(22) International Filing Date:

16 December 2004 (16.12.2004)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:


0329596.1 19 December 2003 (19.12.2003) GB 0406825.0 25 March 2004 (25.03.2004) GB

- (71) Applicant (for all designated States except US): DEPUY INTERNATIONAL LIMITED [GB/GB]; St. Anthony's Road, Beeston, Leeds LS11 8DT (GB).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): HES, Robert [—/BE]; Molenbeemd 16, B-2970 Schilde (BE). CONIX, Bart [—/BE]; Kleine Wandelweg 16, B-2980 Zoersel (BE). GOWLAND, Christopher [GB/GB]; 43 Swanhill Lane, Pontefract, West Yorkshire WF8 2QN (GB).

- (74) Agent: BELCHER, Simon, James; Urquhart-Dykes & Lord LLP, Tower North Central, Merrion Way, Leeds LS2 8PA (GB).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: A BONE SCREW



(57) Abstract: A bone screw (10) having a lead portion (12) and a tail portion (14), each comprising a root and a thread (22, 24) (having a thread lead) formed on the root. The thread on each of the lead and tail portions has an approximately constant diameter along a significant portion of its length. The diameter of the thread on the tail portion is greater than that of the thread on the lead portion, and in which the thread lead of the thread on the lead portion is equal to the thread lead of the thread on the tail portion. The screw can be used to achieve fixation to a vertebra with an anterior approach.

#### 

## Published:

with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.